

PRODUCT TECHNICAL INFORMATION + Instructions for use

Glue-Sealer Dr. Boat

Glue-Sealer Dr. Boat is a polyurethane-based compound that repairs and seals punctures or cuts in inflatable products made of PVC fabric and rubber fabric without the use of patches.

Application area

Repair and sealing of punctures and cuts in inflatable products made of PVC, PU and rubberized fabrics. It doesn't require the use of patches, patches or other patch elements. It is recommended for the repair of inflatable boats, mattresses, water rides, trampolines, as well as cover products made of PVC fabric (tents, tents). Great for repairing promotional PVC banners and truck tents.

Properties. - Resistance to hydrolysis (water resistance) in salt and fresh water.
High strength and heat resistance. Good ductility, including at low temperatures.

Technical specifications.

Polyurethane Based

Colorless, transparent

70 °C heat resistance

Storage

Warranty period of storage 24 months in unopened original packaging

Warning.

The glue is flammable. When using do not smoke, handle away from sources of fire and sparks.
Work with glue in well-ventilated areas.

When transporting at low temperatures, the adhesive viscosity increases, but when it enters a warm area, the adhesive properties are restored without intervention.

Repair of products from PVC or PU fabric and PVC film.

Around the damage - 20 mm in each direction - clean from dirt and dust and wipe with a solvent to remove grease. Let the solvent evaporate (it takes 3-10 minutes)

Large cuts longer than 3 cm in length must first be fastened by stitching the cut place with a thread and needle or by applying a special reinforcing mesh. The damaged place should be put together and then apply a thick layer, covering 10-15 mm areas around the damaged place.

After 20 minutes, reapply a thick layer of glue. After 5 hours, the product can be used. After 24 hours it will be strongly attached.

Repair of rubber products. Before repair, the rubber should be cleaned, covering a section of 10-15 mm in all directions. The rest of the operations are performed as for PVC and PU fabric.

Made in Ukraine. Imported by Poland

Brief instruction

Quick repair of PVC products in any condition WITHOUT PATCHES!

1. Clean damaged area
2. Apply glue on the cut
3. After 20 minutes, reapply 2 more layers of glue
4. Wait 5 hours
5. Ready! Repair completed